

PRODUCT: A-GAIN Exterior Skim/Filler

CODE: 339004

REVISION: 02 **DATE:** 01 October 2017

Amoriguard A-GAIN EXTERIOR SKIM/FILLER is a grey powdered filler based on a blend of grey cement blended with recycled wastes and other mineral fillers. When dealing with new work contracts the smooth white filler often causes difficulties to fully obliterate, resulting in these areas requiring one or two additional coats usually 'spot primed'. *A-GAIN EXTERIOR SKIM/FILLER* is specifically formulated to closer match to the plaster surface, thereby reducing the need for spot prime. It contains 30% recycled materials and is suitable for both interior and exterior use.

Uses and Properties

- ✓ Light Grey colour to better match unpainted plaster.
- ✓ Sandable
- ✓ Low water uptake

Amoriguard A-GAIN EXTERIOR FILLER is carefully formulated using recycled materials from two different waste streams. These materials are used to replace the conventional mineral fillers that would normally be used.

Environmental

Amoriguard is committed to conserving our environment by developing and marketing a range of **Decorative Paint Coatings** and sundries that are both sustainable and eco-friendly.

Technical Data

Binder Type	:	Grey Cement plus powdered polymers
Drying Time	:	Surface Dry: 1 hour (at 23°C and 50% humidity) Hard Dry: 12 hours (at 23°C and 50% humidity)
Drying Process	:	Water evaporation
Over Coating	:	12 hours
Viscosity	:	Powder – mixed to paste of required consistency
Specific Gravity	:	2,24 ±0,15kg/litre
Mass Non Volatile Content	:	100%±2% (dry powder)
Volume Solids	:	N/A – depends on mixing ratio
Spread Rate	:	As required
DFT	:	Depends on thickness applied at
60° Gloss	:	N/A
85° Sheen	:	N/A
Flash Point	:	Water based - Not Applicable
Application Temp	:	>5°C <35°C
Colour Range	:	Light Grey
Clean Equipment With	:	Water
Pack Sizes	:	20kg

Coverage/Spread Rate depends largely on the condition and porosity of the substrate being repaired and manner in which the product is applied.

Application

Correct surface preparation is essential for good product performance and all surfaces should be prepared in the specified manner. Moisture content in the substrate should be as low as possible and we do not recommend painting if it is greater than 15%. Do not apply when ambient temperatures are less than 5°C or greater than 35°C. Add a small quantity of water to *Amoriguard A-GAIN EXTERIOR SKIM/FILLER* and mix well till a thick smooth paste is achieved. Use this for filling cracks and other imperfections. *Amoriguard A-GAIN EXTERIOR*

Amoriguard

SKIM/FILLER can also be thinned marginally more and used as a surface skim to fill the grain and other small imperfections before sanding and painting. After sanding we do suggest priming with either A-GAIN WB Plaster Primer or A-GAIN Waterbased AR Primer before applying finishing coats. Allow to dry for a minimum of 12 hours before overcoating.

Safety instructions

- ✓ Always wear a suitable dust mask and goggles when preparing surfaces.
- ✓ Ensure good ventilation during application and drying.
- ✓ Always keep out of reach of children and animals.
- ✓ If accidental contact with skin, wash immediately with soap and water or a recognised skin cleaner.
- ✓ If accidental contact with eyes, rinse immediately with plenty of water and seek medical advice.
- ✓ Harmful if swallowed. Seek medical attention and do not induce vomiting.

General

Different surfaces and environmental conditions require specific painting systems to produce the best possible results. It is therefore recommended that you contact a Dekro Sales Representative for advice on all your painting requirements whenever possible.

Preventing Problems and General Information

IMPORTANT: Walls (cement plaster, concrete or masonry) must be dry before painting and should not exceed a moisture content of 15% as measured with a Protimeter Surveymaster Moisture Meter or equivalent. The ambient temperatures must be between 5°C and 35°C and humidity between 10% and 85%. Application outside of these parameters could result in poor performance and potential defects and premature failure. Excessive application thickness and/or rapid drying could lead to mud cracking. Avoid applying under adverse weather conditions as this could result in poor product performance. Work from corner to corner, or from a natural cut off point to another.

Cleaning Storage and Disposal

Remove as much material as possible from application equipment and wash immediately after use with water. Close containers tightly after use and store in a cool well-ventilated area away from direct sunlight, heat or severe cold and damp conditions. Do not empty contents or wash water into drains or water courses. Amoriguard encourages you to recycle the plastic bucket after use and to dispose of wash water and paint residues in a responsible manner that complies with local regulations

THE TECHNICAL DATA FURNISHED IS GIVEN TO THE BEST OF OUR KNOWLEDGE BASED ON CONTROLLED LABORATORY TESTS UNDER IDEAL APPLICATION CONDITIONS. NO GUARANTEE OF ANY PERFORMANCE CHARACTERISTIC IS THEREFORE GIVEN OR IMPLIED AND WE DO NOT HOLD OURSELVES RESPONSIBLE FOR ANY CONSEQUENTIAL DAMAGE OF WHATSOEVER NATURE THAT MAY ARISE FROM USE OF OUR PRODUCTS. IN THE EVENT OF A PROVEN PRODUCT FAULT OUR LIABILITY WILL BE LIMITED TO THE REPLACEMENT OF THE PRODUCT ONLY. IT IS THE USER'S RESPONSIBILITY TO CONFIRM THE CURRENCY OF PRODUCT DATA SHEETS.

MANUFACTURED IN SOUTH AFRICA FOR AMORIGUARD BY DEKRO PAINTS (PTY) LTD. 24 FABRIEK STREET, KUILSRIVER, 7590.
DEKRO PAINTS IS A SABS ISO 9001 CERTIFIED COMPANY