

## HIGH GLOSS ENAMEL

CODE: 190300

REVISION: 02

DATE: 22 March 2018

### GENERAL DESCRIPTION

- Economical enamel for interior and exterior use.
- Good appearance with a high gloss.
- Reasonable durability and gloss retention.
- Available in white only.
- Especially formulated for the paint contractor.

### USES

- Recommended for the protection and decoration of interior and exterior surfaces.
- Appropriate primers and undercoats must always be used, particularly on new work.
- An economic market-related product in quality and performance.

### TECHNICAL DATA

Type	:	Synthetic alkyd resin
Drying Time	:	Surface : 3-4 hours (at 23°C and 50% relative humidity).
	:	Hard Dry: 10-12 hours (at 23°C and 50% relative humidity).
Recoating	:	Overnight
Viscosity	:	95 – 105 K $\mu$
Specific Gravity	:	1,00 – 1,05
Weight solids	:	30% – 35%
Volume solids	:	27% – 32%
Spreading rate	:	5m <sup>2</sup> – 6m <sup>2</sup> /litre (to obtain a continuous film without coverage)
Flash point	:	Over 21°C
Colour range	:	White only
Packing size	:	5 litre

### APPLICATION PROCESS

- Ready for use with brush or roller.
- For spray application, thin with Spraying Enamel Thinners or Mineral Turps.
- Thinning – not recommended, except for application by spray.
- Equipment cleaning – Mineral Turps

The technical data furnished is given to the best of our knowledge based on controlled laboratory tests under ideal application conditions. No guarantee of any performance characteristic is therefore given or implied and we do not hold ourselves responsible for any consequential damage of whatsoever nature that may arise from use of our products. In the event of a proven product fault our liability will be limited to the replacement of the product only. It is the user's responsibility to confirm the currency of product data sheets.

e-mail: [info@dekro.co.za](mailto:info@dekro.co.za)

Toll Free: 0800 222 423

<http://www.dekro.co.za>