

**HYDROGLAZE**  
**Product Code : 109005**  
(Page 1 of 2)

**DESCRIPTION**

Pure Acrylic water-based sealer and glaze coat which dries to a water white clear film.

**USES**

Sealer for cement based surfaces.  
A water white glaze coat.  
A bonding agent before tiling or laying cement screeds.

**ADVANTAGES**

Water white when dry.  
For interior and exterior use.  
Excellent water resistance.  
Excellent adhesion to cement and other primed surfaces.  
Bonds powdery surfaces.  
Easy to use and economical.  
Non-toxic.  
Non-flammable.

**COVERAGE**

Approximately 8 – 10m<sup>2</sup> per litre, depending on application

**TECHNICAL DATA**

Type	:	Pure Acrylic	
Viscosity	:	75 – 80 sec. FC4	
S.G.	:	1,00 – 1,05	
Drying	:	Surface dry	: 1 hr @ 23°C
		Hard dry	: 6 hrs @ 23°C
		Re-coating	: 2 hrs @ 23°C
Appearance	:	Clear, glossy finish.	
Solids	:	Weight	32 – 34%
		Volume	31 - 33%
Shelf life	:	12 months.	
Service temps.	:	-10°C to 60°C	
Colour	:	Milky when wet, dries clear.	
Application	:	Brush, roller or spray.	
Clean up	:	With water.	

**HYDROGLAZE**  
**Product Code : 109005**  
(Page 2 of 2)

**APPLICATION**

All surfaces should be clean, dry and free of grease or contaminants.

**New Cement Surfaces**

Allow to cure for 4 weeks. Rinse clean with fresh water. When dry apply Hydroglaze thinned 20% with water. Apply a second coat unthinned.

**Old Cement Surfaces**

Rinse clean with fresh water. When dry apply Hydroglaze thinned 20% with water. Apply a 2<sup>nd</sup> coat unthinned.

**Painted Surfaces**

Apply direct to acrylics. Enamels should first be abraded.

**Clay Bricks**

Rinse clean with fresh water. When dry apply Hydroglaze thinned 20% with water. Apply a 2<sup>nd</sup> coat unthinned.

**Other Surfaces**

Contact the Dekro Technical Department first.

**SAFETY**

Inhalation	:	Move to fresh air.
Skin	:	Wash with soap and water.
Eyes	:	Rinse with plenty of water. Seek medical attention if symptoms persist.
Ingestion	:	Give plenty of water/milk. Induce vomiting if patient conscious. Get medical advice.

For further details refer to the product MSDS.

**LIMITATIONS**

The product turns slightly milky when it is wet but dries again to a clear finish.

Not for internal consumption. Keep out of the reach of children.

Do not attempt to paint outside if rain is imminent.

The technical data furnished is given to the best of our knowledge based on controlled laboratory tests under ideal application conditions. No guarantee of any performance characteristic is therefore given or implied and we do not hold ourselves responsible for any consequential damage of whatsoever nature that may arise from use of our products. In the event of a proven product fault our liability will be limited to the replacement of the product only. It is the users responsibility to confirm the currency of product data sheets.