

METALLIC ZINC RICH
PRIMER

PRODUCT CODE: 810012 – LIGHT GREY
(Page 1 of 1)

GENERAL DESCRIPTION:

Metallic Zinc Rich Primer is a general purpose zinc primer for the temporary protection of suitably prepared steel structures.

TECHNICAL DATA:

Colour	:	Light Grey
Mixing Ratio	:	Single Pack
Drying Time	:	Touch Dry 20 minutes
		Dry to recoat 2 hours
Practical Coverage	:	6 – 8m ² / litre
Thinning Solvent	:	Spraying Enamel Thinners

APPLICATION INSTRUCTIONS:

- Ensure that the substrate is clean, dry and free from any oil, grease and other surface contaminants.
- Steel may be cleaned by means of steam cleaning or wiping with Lacquer Thinners.
- Apply 1 coat of Metallic Zinc Rich Primer by means of brush or spray equipment and allow -minimum 2 hours to dry.
- Apply the second or top coat within 48 hours of priming.

The technical data furnished is given to the best of our knowledge based on controlled laboratory tests under ideal application conditions. No guarantee of any performance characteristic is therefore given or implied and we do not hold ourselves responsible for any consequential damage of whatsoever nature that may arise from use of our products. In the event of a proven product fault our liability will be limited to the replacement of the product only. It is the users responsibility to confirm the currency of product data sheets.

FOR FURTHER INFORMATION PLEASE CONTACT: (TOLL FREE) 0800 222 423

Website: www.dekro.co.za e-mail: info@dekro.co.za