

**SHEERFLEX**  
**PRODUCT CODE : 124001**  
(Page 1 of 1)**GENERAL DESCRIPTION :**

Most textured coats contain sand, silicate, mica or other coarse particles. These are used to assist in the textured appearance and to bridge cracks. The disadvantage is that these coatings have a high degree of dirt retention.

Sheerflex is specially formulated to give a textured appearance and bridge cracks without being too rough. This results in a coating that has a low dirt retention giving a much longer coating life.

**USES :**

Sheerflex should be used where outstanding durability and waterproofing properties are required. Sheerflex is designed to cover hair cracks on old and crazed plaster.

**TECHNICAL DATA :**

Type	-	Acrylic co-polymer emulsion
Drying Time	-	Surface : 1 - 1,5 hours (at 23°C and 50% relative humidity)
	-	Hard dry : 3 - 4 hours (at 23°C and 50% relative humidity)
Overcoating	-	4 hours
Viscosity	-	93-95K $\mu$ (ROD)
Volume Solids	-	41%-43% (100 $\mu$ wet film will give dry film)
Gloss	-	Sheen
Spreading Rate	-	6 m <sup>2</sup> - 7m <sup>2</sup> /litre (to obtain a continuous film without full coverage)
Flash Point	-	Not applicable
Colour Range	-	White, range of standard colours as per current colour card.
Packing Size	-	5 litre, 20 litre

All above technical data is based on Sheerflex - white only. Coverage/spreading rate of colours depends on condition and porosity of the surface and the manner in which Sheerflex is applied and used. For best results do not exceed a spreading rate of 6m<sup>2</sup> per litre.

**APPLICATION :**

	-	Ready for use with brush or roller.
Thinning	-	Sheerflex must not be thinned under any circumstances.
Equipment Cleaning	-	Water.

The technical data furnished is given to the best of our knowledge based on controlled laboratory tests under ideal application conditions. No guarantee of any performance characteristic is therefore given or implied and we do not hold ourselves responsible for any consequential damage of whatsoever nature that may arise from use of our products. In the event of a proven product fault our liability will be limited to the replacement of the product only. It is the user's responsibility to confirm the currency of product data sheets.