

SUPER PAINT STRIPPER

PRODUCT CODE: 096104

(Page 1 of 2)

GENERAL DESCRIPTION

- General purpose paint remover.
- Non-flammable.
- Low wax content.
- Rinses off with water.

USES

- Recommended for removing previously painted or varnished surfaces of metal, wood or plaster.
- Plastic surfaces must be tested first before using Super Paint Stripper.

TECHNICAL DATA

Type	Methylene chloride, balanced blend of surfactants and solvents.
Drying time	N/A
Viscosity	83 – 85 Ku's
Specific gravity	1.18 – 1.20
Spreading rate	1 litre will remove approx. 8m ² of a single layer of paint.
Flash point	Not flammable.
Packing size	1 litre, 5 litre

All above technical data is based on practical experience and depends on condition, number of layers of paint, type of paint and the manner in which Super Paint Stripper is applied and used.

APPLICATION

- | | |
|--------------------|---|
| | - Ready for use with brush or roller. |
| Thinning | - N/A |
| Equipment cleaning | - Water, then follow with a wash of Mineral Turps |

STANDARD APPLICATION PROCEDURES

- Apply a liberal coat of Super Paint Stripper.
- Leave up to 30 minutes, and then scrape off old paint.
- Where multiple coats of paint are present apply a second coat of Super Paint Stripper.
- Leave for the same interval and then scrape off old paint.
- After scraping off all paint, wash liberally with water or hose down with water.
- Finally wash with Mineral Turps to remove all traces of wax.
- Allow sufficient time to dry before surface preparation work begins.

SUPER PAINT STRIPPER

PRODUCT CODE: 096104

(Page 2 of 2)

GENERAL

- Different surfaces and environmental conditions require specific painting systems to produce the best possible results.
- It is therefore recommended that you contact a sales representative for advice on all your painting requirements whenever possible.

PRECAUTIONS

- Apply only in well-ventilated areas.
- Avoid contact with skin and protect your eyes.
- Do not apply to plastic without testing on a small area.
- Rubber gloves and protective eye shields should be worn during the cleaning operation.
- Do not smoke or inhale fumes during the application. This recommendation is in line with international safety precautions.

The technical data furnished is given to the best of our knowledge based on controlled laboratory tests under ideal application conditions. No guarantee of any performance characteristic is therefore given or implied and we do not hold ourselves responsible for any consequential damage of whatsoever nature that may arise from use of our products. In the event of a proven product fault our liability will be limited to the replacement of the product only. It is the users responsibility to confirm the currency of product data sheets.

FOR FURTHER INFORMATION PLEASE CONTACT: (TOLL FREE) 0800 222 423

Website: www.dekro.co.za

e-mail: info@dekro.co.za