

SUPER PAINT STRIPPER

Page 1 of 2

CODE: 096104

REVISION: 02

DATE: 03 February 2026

GENERAL DESCRIPTION

Super Paint Stripper is a general-purpose Methylene Chloride based paint remover which is non-flammable and has a low wax content.

USES AND PROPERTIES

It is recommended for removing previously painted or varnished surfaces on metal, wood or plaster. Plastic surfaces must be tested first before using **Super Paint Stripper**.

TECHNICAL DATA

Binder Type	:	Methylene chloride, balanced blend of surfactants and solvents
Viscosity	:	90 - 95KU
Specific Gravity	:	1.19 ±0,025kg/litre
Mass Solids	:	3% ±0,2%
Volume Solids	:	4% ±0,2%
Coverage	:	4m ² /litre
Clean Equipment With	:	Soap and water
Pack Sizes	:	1 litre, 5 litre

Coverage/spreading rate of **Super Paint Stripper** depends largely on the condition and porosity of the substrate being painted and manner in which the product is applied.

APPLICATION

Correct surface preparation is essential for good product performance and all surfaces should be prepared as per the standard Dekro Preparation Specifications. Copies of these are available on request from Dekro Paints or can be downloaded from our website - www.dekro.co.za.

- Apply a liberal coat of **Super Paint Stripper**.
- Leave up to 30 minutes and then scrape off old paint.
- Where multiple coats of paint are present apply a second coat of **Super Paint Stripper**.
- Leave for the same interval and then scrape off old paint.
- After scraping off all paint, wash liberally with water or hose down with water.
- Allow sufficient time to dry before surface preparation work begins.
- Large areas – cover with plastic while reacting.

SAFETY INSTRUCTIONS

Always keep out of reach of children and animals.

Wear a suitable dust mask and goggles when preparing surfaces.

Rubber gloves and protective eye shields should be worn during the cleaning operation.

Ensure good ventilation during application and drying.

If accidental contact with skin, wash immediately with soap and water or a recognised skin cleaner.

If accidental contact with eyes, rinse immediately with plenty of water and seek medical advice.

Harmful if swallowed. Seek medical attention and do not induce vomiting.



SUPER PAINT STRIPPER

Page 2 of 2

GENERAL

Different surfaces and environmental conditions require specific painting systems to produce the best possible results.

It is therefore recommended that you contact a Dekro Sales representative for advice on all your painting requirements whenever possible.

PREVENTING PROBLEMS AND GENERAL INFORMATION

The ambient temperature must be between 4°C and 40°C and humidity between 10% and 85%.

Avoid applying under adverse weather conditions as this could result in poor product performance.

Excessively friable surfaces should be cleaned down prior to primer application.

To ensure consistent appearance ensure that the batch numbers on all containers used are the same.

Where batch numbers on containers differ, intermix containers before use.

CLEANING, STORAGE AND DISPOSAL

Remove as much paint as possible from application equipment and wash immediately after use with soap and water.

Close containers tightly after use and store in a cool well-ventilated area.

Do not empty contents or wash into drains or water courses.

When disposing please follow local authorities regulations and recycle the container after use.

Avoid storing in direct sunlight and heat.



DEKRO
IS THE ARCHITECTS CHOICE

The technical data furnished is given to the best of our knowledge based on controlled laboratory tests under ideal application conditions. No guarantee of any performance characteristic is therefore given or implied and we do not hold ourselves responsible for any consequential damage of whatsoever nature that may arise from use of our products. In the event of a proven product fault our liability will be limited to the replacement of the product only. It is the user's responsibility to confirm the currency of product data sheets.

e-mail: info@dekro.co.za

Toll Free: 0800 222 423

<http://www.dekro.co.za>

