

WUNDA CLEAN

Page 1 of 2

CODE: 096119

REVISION: 02

DATE: 03 February 2026

GENERAL DESCRIPTION

A solvent-based degreaser which can be diluted and rinsed off with water.

USES AND PROPERTIES

- Degreasing and cleaning of cement floors, metal and other surfaces.
- Cleans brushes which have dried paint on them.

TECHNICAL DATA

Binder Type	:	Blend of surfactants and solvents
Viscosity	:	10 - 12" Ford Cup No. 4
Specific Gravity	:	0.819 +-0,025
Mass Non-Volatile Content	:	9%
Volume Solids	:	8%
Coverage	:	Coverage will vary significantly depending on the amount of grease to be removed. Light grease: 20m ² /litre (typical) Moderate grease: 10m ² /litre (typical) Heavy grease: ±5m ² /litre (typical)
Pack Sizes	:	1 litre, 5 litre

APPLICATION

Correct surface preparation is essential for good product performance and all surfaces should be prepared as per the standard Dekro Preparation Specifications. Copies of these are available on request from Dekro Paints or can be downloaded from our website - www.dekro.co.za.

Heavy grease	:	Apply Wunda Clean without thinning. If the grease is very heavy and hard then several applications may be required.
Light grease	:	Apply Wunda Clean , thinned 50% with water.
General cleaning	:	Apply Wunda Clean , thinned 90% with water.
Application method	:	Brush, mop, broom or cloth and work well into the surface. Rinse with clean water.

SAFETY INSTRUCTIONS

Always keep out of reach of children and animals.

Wear a suitable dust mask and goggles when preparing surfaces.

Ensure good ventilation during application and drying.

If accidental contact with skin, wash immediately with soap and water or a recognised skin cleaner.

If accidental contact with eyes, rinse immediately with plenty of water and seek medical advice.

Harmful if swallowed. Seek medical attention and do not induce vomiting.



WUNDA CLEAN

Page 2 of 2

GENERAL

Different surfaces and environmental conditions require specific painting systems to produce the best possible results.

It is therefore recommended that you contact a Dekro Sales representative for advice on all your painting requirements whenever possible.

CLEANING, STORAGE AND DISPOSAL

Remove as much paint as possible from application equipment and wash immediately after use with water. Close containers tightly after use and store in a cool well-ventilated area.

Do not empty contents or wash into drains or water courses.

When disposing please follow local authorities regulations and recycle the container after use.

Avoid storing in direct sunlight and heat.

Technical Data Sheet



DEKRO
IS THE ARCHITECTS CHOICE

The technical data furnished is given to the best of our knowledge based on controlled laboratory tests under ideal application conditions. No guarantee of any performance characteristic is therefore given or implied and we do not hold ourselves responsible for any consequential damage of whatsoever nature that may arise from use of our products. In the event of a proven product fault our liability will be limited to the replacement of the product only. It is the user's responsibility to confirm the currency of product data sheets.

e-mail: info@dekro.co.za

Toll Free: 0800 222 423

<http://www.dekro.co.za>

